




AQUILA LITE

Quadrifilar Helical GNSS Antenna (No enclosure)

CZ0069-6G01

Key Features

- Multi constellation reception for GPS, GLONASS, BDS, and Galileo
- Wideband support for L1 L2 L5, E1 E5 E6, B1 B2 B3 draw
- RHCP polarization with low axial ratio
- Integrated low noise amplifier with 35 dB typical gain
- DC input range from 3 to 15 V
- Compact helix structure for stable phase center performance
- SMA male connector
- Operating temperature from minus 45°C to plus 85°C

1 Introduction

AQUILA LITE is a compact, high performance Active Quadrifilar Helical GNSS Antenna designed for applications that demand reliable multi band positioning in a reduced form factor. With a shortened 40 mm body, AQUILA LITE integrates a carefully engineered RHCP helix to deliver stable phase characteristics and consistent gain across all major global navigation satellite systems. It supports GPS L1 L2 L5, GLONASS L1 L2 L3, BDS B1 B2 B3, and Galileo E1 E5 E6, ensuring dependable performance in space constrained designs where signal conditions may vary.

An integrated low noise amplifier improves sensitivity and signal acquisition, maintaining robust GNSS lock even in challenging RF environments. Compared with other compact helical GNSS antennas, AQUILA LITE offers wideband capability, strong RHCP purity, and stable electrical performance, now delivered in a lighter, shorter mechanical form.

Features

- ◆ Multi constellation reception for GPS, GLONASS, BDS, and Galileo
- ◆ Wideband support for L1 L2 L5, E1 E5 E6, B1 B2 B3 draw
- ◆ RHCP polarization with low axial ratio
- ◆ Integrated low noise amplifier with 35 dB typical gain
- ◆ DC input range from 3 to 15 V
- ◆ Compact helix structure for stable phase center performance
- ◆ SMA male connector
- ◆ Operating temperature from minus 45°C to plus 85°C

Applications

- ◆ Compact high precision GNSS receivers
- ◆ Survey and mapping equipment
- ◆ Precision agriculture systems
- ◆ Industrial timing and synchronization
- ◆ UAV, robotics, and autonomous platforms
- ◆ Asset tracking and fleet positioning

2 Mechanical Specifications

Part Number	CZ0069-6G01
Name	AQUILA LITE (No enclosure)
Dimensions (mm)	39.6 × 39.8 Ø
Weight	< 30 g
Antenna Type	Quadrifilar Helical GNSS Antenna
Connector*	SMA Male
Housing	None

Alternate cable length and connectors available on request

3 Electrical / RF Specifications

Band	Frequency Range (MHz)	Peak Gain (dBic)	Out-ofband Rejection	Axial Ratio	Impedance
L5, E5a, E5b, E5, B2a, B2b, B2, L2, L2, E6	1164-1278	>2.00	>35	≤1.5	50 ohm
L1, E1, B1, G1, L band (SBAS), B1C, E2-L1-E	1525-1615		>40		

4 LNA Specifications

Frequency Range (MHz)	DC Voltage (V)	Current (mA) Typical	Gain (dB) Typical	VSWR	Noise Figure (dB)
1164-1278	3 - 15	20	33	≤2.00	≤2.00
1525-1615					


5 Environmental

Operational Temperature	-45 to +85°C
Storage Temperature	-45 to +85°C
Relative Humidity (Storage)	65±20% RH
IP Rating	IP67
RoHS and REACH compliant	Yes

3 2D Polar Plots

FREQUENCY RANGE: 1176 - 1268 MHZ

Elevation Radiation Pattern @ L2 ($\phi = 0^\circ$)




Passive Antenna Vertical Plane Radiation Pattern @ L2

Frequency (MHz)	Polarization	Peak Gain (dBi)	HPBW (3dB) (Deg)
1176	RHCP	-1.3	112
1192		0.6	109
1207		2.3	114
1227		3.1	108
1246		2.4	107
1268		0.5	119

4 2D Polar Plots

FREQUENCY RANGE: 1561 - 1602 MHZ

Elevation Radiation Pattern @ L1 ($\phi = 0^\circ$)



Passive Antenna Vertical Plane Radiation Pattern @ L1


Frequency (MHz)	Polarization	Peak Gain (dBi)	HPBW (3dB) (Deg)
1561	RHCP	2.6	108
1575		2.9	107
1602		2.9	94

5 2D Polar Plots

FREQUENCY RANGE: 1176 - 1268 MHZ

Azimuth Radiation Pattern @ L2 ($\theta = 90^\circ$)

Azimuth radiation pattern shown to illustrate radiation uniformity around 360 degrees



RHCP Circularity in Azimuth Plane @ L2


Frequency (MHz)	Circularity (dB)
1176	1.2
1192	1.0
1207	0.9
1227	0.8
1246	0.9
1268	0.8

6 2D Polar Plots

FREQUENCY RANGE: 1561 - 1602 MHZ

Azimuth Radiation Pattern @ L1 ($\theta = 90^\circ$)

Azimuth radiation pattern shown to illustrate radiation uniformity around 360 degrees




RHCP Circularity in Azimuth Plane @ L1

Frequency (MHz)	Circularity (dB)
1561	1.2
1575	1.2
1602	1.2

Circularity values represent RHCP polarization uniformity in the azimuth plane. Lower values indicate improved circular polarization performance.

7 Mechanical Drawing



1.ELECTRICAL PROPERTIES :

- 1.1 Frequency Range.....1164~1278MHz&1525~1615MHz
- 1.2 Impedance.....50 Ohm Nominal
- 1.3 VSWR.....2.0(Max)
- 1.4 LNA Gain.....35±3dB
- 1.5 DC Voltage.....3~16V(3.3V or 5.0V recommend)


- 2.Operating Temp: -40°C~+85°C
- 3.These Products are in conformity with ROHS 2.0
- 4.Important dimensions marked "*"

UNIT
mm

2	Connector	SMA, Male;Gold Plated
1	Antenna	Inner antenna
NO	DESCRIPTION	


8 Phase Centre Reference

The antenna phase centre is located on the mechanical axis as defined in the associated mechanical drawing. Due to the quadrifilar helical structure, the phase centre behaviour is inherently stable across elevation angles.



9 Axial Ratio


Axial Ratio at Zenith @ L2



Frequency (MHz)	Axial Ratio at Zenith (dB)
1176	1.3
1192	1.0
1207	0.8
1227	0.7
1246	0.7
1268	0.5


10 Axial Ratio

Axial Ratio at Zenith @ L1



Frequency (MHz)	Axial Ratio at Zenith (dB)
1561	1.0
1575	1.1
1602	1.2

11 LNA Gain / VSWR



12 Packaging

Antennas packed in PE bag (1 per bag)

Bulk (units individually bagged and boxed; standard carton quantity: 50)

13 Material Regulation

The antenna has been assessed to conform to RoHS requirements. A certificate of conformance is available upon request.

Synzen Precision Technology Ltd makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Synzen reserves all rights to this document and the information contained herein. Reproduction, use or disclosure to third parties without express permission is strictly prohibited.